NSN 5320-01-415-5430

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-5430 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 3.175 inches and 3.195 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.5141 inches and 0.5151 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2207 inches and 0.2242 inches **Grip Length:** Between 2.495 inches and 2.505 inches Min. Tensile Strength (psi): 25600 pounds per square inch **Thread Size:** 0.500 inches **Shear Strength:** 39600 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Color black on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Cagec 73197, specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-415-5430

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0