## NSN 5320-01-415-5500

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-5500 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.385 inches and 2.405 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.094 inches and 0.096 inches **Shank Diameter:** Between 0.248 inches and 0.249 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.995 inches and 2.005 inches Min. Tensile Strength (psi): 5820 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5320-01-415-5500

Pin-rivet - Page 2 of 2



Fiig:

A528u0