
# NSN 5320-01-415-6135

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Identification Code Color:

Black

#### Fastener Length:

Between 2.385 inches and 2.405 inches

#### **Head Style:**

Flush countersunk

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.2016 inches and 0.2026 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3765 inches and 0.3813 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 2.390 inches and 2.400 inches

#### Thread Size:

0.3125 inches

#### **Countersink Angle:**

100.0 degrees

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4927 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

294, cagec 73197 mfr ref single treatment response

#### **Thread Series Designator:**

Unjf

### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-01-415-6135

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

