## NSN 5320-01-415-8603

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-8603

Thread Class:

**Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.500 inches and 1.520 inches **Head Style:** Err-090 **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.472 inches and 0.505 inches Lubrication: Cetyl alcohol **End Application:** Pacer dawn **Grip Length:** 0.875 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** 294, fscm 73197 mfr ref single treatment response **Thread Series Designator:** 

Unjf

## NSN 5320-01-415-8603

Pin-rivet - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0