## NSN 5320-01-416-0483

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-416-0483 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.945 inches and 0.955 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style: Head Major Diameter:** Between 0.2966 inches and 0.3016 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.620 inches and 0.630 inches Min. Tensile Strength (psi): 2000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 6130 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** 1/64 "oversize shank" for repair work only. Oversize shank Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5320-01-416-0483

Pin-rivet - Page 2 of 2



Fiig:

A528u0