## NSN 5320-01-416-0484

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-416-0484 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.578 inches and 1.588 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.5066 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.183 inches and 1.193 inches **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100 0 degrees nse se

100.0 degrees
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material respon
Surface Treatment:
Passivate
Surface Treatment Specification:
258 fscm 73197 mfr ref single treatment respon
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5320-01-416-0484

Pin-rivet - Page 2 of 2



Fiig:

A528u0