NSN 5320-01-416-0535

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-416-0535 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.035 inches and 1.055 inches **Head Style:** Err-090 **Head Height:** Between 0.020 inches and 0.030 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.4047 inches and 0.4057 inches **Shank Style: Head Major Diameter:** Between 0.550 inches and 0.585 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.495 inches and 0.505 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.406 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi-kote 1, aluminum coating 294 per hi-shear mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-416-0535

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0