

View Online at <https://aerobasegroup.com/nsn/5320-01-416-1696>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2900 inches and 0.2910 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.463 inches

Expansion Device:

Threaded sleeve

Lubrication:

Wax or cetyl alcohol or solid film

End Application:

T-38a acft

Grip Length:

Between 0.407 inches and 0.469 inches

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Il-s-6758 federal specification 10th material response bolt or il-s-5626 federal standard 10th material response bolt or il-s-6049 military specification 10th material response bolt

Surface Treatment:

Cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

spec.