# NSN 5320-01-416-1702

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-416-1702

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.2900 inches and 0.2910 inches

## Shank Style:

Threaded self-plugging shank w/sleeve

## Head Major Diameter:

0.463 inches

#### Expansion Device:

Threaded sleeve

#### Lubrication:

Wax or cetyl alcohol or solid film

#### End Application:

T-38a acft

Grip Length:

Between 0.595 inches and 0.656 inches

#### Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

# Material Specification:

II-s-6758 federal specification 10th material response bolt or iI-s-5626 federal standard 10th material response bolt or iI-s-6049 military

specification 10th material response bolt

# Surface Treatment:

Cadmium sleeve

## Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response nut

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A040a0

Mil-std (military Standard):

spec.