

View Online at <https://aerobasegroup.com/nsn/5320-01-416-4288>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2290 inches and 0.2300 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

0.342 inches

**Expansion Device:**

Threaded sleeve

**Lubrication:**

Wax or cetyl alcohol or solid film

**End Application:**

T-38a acft

**Grip Length:**

Between 0.282 inches and 0.344 inches

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Original name: fastener

**Material:**

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

**Material Specification:**

II-s-6758 federal specification 10th material response bolt or II-s-5626 federal standard 10th material response bolt or II-s-6049 military specification 10th material response bolt

**Surface Treatment:**

Cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, type 1, class 3 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

spec.