## NSN 5320-01-416-4881

Blind Rivet - Page 1 of 1

A040a0

spec.

Mil-std (military Standard):



View Online at https://aerobasegroup.com/nsn/5320-01-416-4881 **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.2290 inches and 0.2300 inches **Head Major Diameter:** 0.342 inches **Expansion Device:** Threaded sleeve Lubrication: Cetyl alcohol or cetyl alcohol or solid film **End Application:** T-38a acft **Grip Length:** Between 0.345 inches and 0.406 inches Hardness Rating: 39.0 rockwell c nut and 43.0 rockwell c nut **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Original name: fastener Material: Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut **Material Specification:** II-s-6758 federal specification 10th material response bolt or iI-s-5626 federal standard 10th material response bolt or iI-s-6049 military specification 10th material response bolt **Surface Treatment:** Cadmium sleeve **Surface Treatment Specification:** Qq-p-416, type 1, class 3 federal specification single treatment response sleeve Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: