NSN 5320-01-416-5184

Blind Rivet - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/5320-01-416-5164
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.2290 inches and 0.2300 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.342 inches
Expansion Device:
Threaded sleeve
Lubrication:
Wax or cetyl alcohol or solid film
End Application:
T-38a acft
Grip Length:
Between 0.595 inches and 0.656 inches
Hardness Rating:
39.0 rockwell c nut and 43.0 rockwell c nut
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Original name: fastener
Material:
Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut
Material Specification:
II-s-6758 federal specification 10th material response bolt or iI-s-5626 federal standard 10th material response bolt or iI-s-6049 military
specification 10th material response bolt
Surface Treatment:
Cadmium sleeve
Surface Treatment Specification:
Qq-p-416, type 1, class 3 federal specification single treatment response sleeve
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A040a0

spec.

Mil-std (military Standard):