

View Online at <https://aerobasegroup.com/nsn/5320-01-416-9836>

Fastener Length:

1.041 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Head Height:

0.077 inches

Shank Diameter:

Between 0.202 inches and 0.203 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.342 inches

Expansion Device:

Threaded stem

Lubrication:

Grease film

End Application:

T-38a acft

Grip Length:

Between 0.282 inches and 0.344 inches

Min. Tensile Strength (psi):

1400 pounds per square inch

Hardness Rating:

39.0 rockwell c and 45.0 rockwell c

Shear Strength:

5240 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Original name-fastener

Material:

Steel comp 4130 body or steel comp 4140 body or steel comp 8740 body

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or qq-s-763 federal specification 2nd material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416 type 2 cl2 federal specification single treatment response body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.