# NSN 5320-01-416-9836

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-416-9836

# Fastener Length:

1.041 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

#### **Head Height:**

0.077 inches

### Shank Diameter:

Between 0.202 inches and 0.203 inches

#### Shank Style:

Threaded self-plugging shank w/sleeve

#### Head Major Diameter:

0.342 inches

**Expansion Device:** 

Threaded stem

#### Lubrication:

Grease film

# End Application:

T-38a acft

#### Grip Length:

Between 0.282 inches and 0.344 inches

#### Min. Tensile Strength (psi):

1400 pounds per square inch

#### Hardness Rating:

39.0 rockwell c and 45.0 rockwell c

#### Shear Strength:

5240 double pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Original name-fastener

#### Material:

Steel comp 4130 body or steel comp 4140 body or steel comp 8740 body

#### Material Specification:

Qq-s-763 federal specification 1st material response sleeve or qq-s-763 federal specification 2nd material response sleeve or ams 5639 assn

standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

#### Surface Treatment:

Cadmium stem

#### **Surface Treatment Specification:**

Qq-p-416 type 2 cl2 federal specification single treatment response body

## Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5320-01-416-9836

Blind Rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.

