# NSN 5320-01-417-1031

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-417-1031



Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.052 inches and 1.072 inches

# Head Style:

Err-090

#### Head Height:

Between 0.037 inches and 0.047 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.242 inches and 0.262 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

Between 0.745 inches and 0.755 inches

#### Min. Tensile Strength (psi):

1940 pounds per square inch

### Thread Size:

0.164 inches

### Shear Strength:

4010 single pounds per square inch

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response

#### Surface Treatment:

Passivate

## **Thread Series Designator:**

Unjc

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-417-1031

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

