

View Online at <https://aerobasegroup.com/nsn/5320-01-417-2411>

**Fastener Length:**

1.166 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Head Height:**

0.077 inches

**Shank Diameter:**

Between 0.202 inches and 0.203 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

0.342 inches

**Expansion Device:**

Threaded stem

**Lubrication:**

Grease film

**End Application:**

T-38a acft

**Grip Length:**

Between 0.407 inches and 0.469 inches

**Min. Tensile Strength (psi):**

1400 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 45.0 rockwell c

**Shear Strength:**

5240 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Original name-fastener

**Material:**

Steel comp 4130 body or steel comp 4140 body or steel comp 8740 body

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or qq-s-763 federal specification 2nd material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416 type 2 cl2 federal specification single treatment response body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.