NSN 5320-01-419-4517

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-419-4517



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.7225 inches and 1.7425 inches

Head Style:

Err-090

Head Height:

Between 0.078 inches and 0.088 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.1825 inches and 1.1925 inches

Min. Tensile Strength (psi):

14100 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

32000 double pounds per square inch

Special Features:

Color white on top of head.

Material:

Cobalt comp mp-35-n

Material Specification:

Ams5844 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

73197-hl932 manufacturers standard

NSN 5320-01-419-4517

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

