

View Online at <https://aerobasegroup.com/nsn/5320-01-419-4517>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.7225 inches and 1.7425 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.078 inches and 0.088 inches

**Width Between Flats:**

Between 0.1582 inches and 0.1617 inches

**Shank Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.565 inches and 0.600 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 1.1825 inches and 1.1925 inches

**Min. Tensile Strength (psi):**

14100 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

32000 double pounds per square inch

**Special Features:**

Color white on top of head.

**Material:**

Cobalt comp mp-35-n

**Material Specification:**

Ams5844 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

73197-hl932 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0