

View Online at <https://aerobasegroup.com/nsn/5320-01-420-0969>

Fastener Length:

0.265 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.092 inches and 0.097 inches

Shank Style:

Self-plugging high clinch shank

Head Major Diameter:

Between 0.179 inches and 0.183 inches

Grip Length:

Between 0.126 inches and 0.187 inches

Min. Tensile Strength (psi):

155 pounds per square inch

Shear Strength:

105 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 1008 or steel comp 1012 or steel comp 1018

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Test Data Document:

81349-mil-r8814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms20605 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0