

View Online at <https://aerobasegroup.com/nsn/5320-01-420-0972>

**Fastener Length:**

0.390 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.092 inches and 0.097 inches

**Shank Style:**

Self-plugging high clinch shank

**Head Major Diameter:**

Between 0.179 inches and 0.183 inches

**Grip Length:**

Between 0.251 inches and 0.312 inches

**Min. Tensile Strength (psi):**

155 pounds per square inch

**Shear Strength:**

105 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 1008 or steel comp 1012 or steel comp 1018

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Test Data Document:**

81349-mil-r8814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

96906-ms20605 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0