## NSN 5320-01-422-0481

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-422-0481 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.010 inches and 1.030 inches **Head Style:** Err-090 **Head Height:** Between 0.078 inches and 0.088 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3804 inches and 0.3815 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.565 inches and 0.600 inches Lubrication: Solid film and cetyl alcohol **Grip Length:** Between 0.375 inches and 0.385 inches Min. Tensile Strength (psi): 8700 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 21500 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Anodize **Thread Series Designator:** Unjf **Specification Data:** 26512-gb511bc manufacturers standard Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-422-0481

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0