

View Online at <https://aerobasegroup.com/nsn/5320-01-422-0636>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.178 inches and 1.198 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.102 inches and 0.112 inches

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3427 inches and 0.3432 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.490 inches and 0.520 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.683 inches and 0.693 inches

**Min. Tensile Strength (psi):**

9200 pounds per square inch

**Thread Size:**

0.3125 inches

**Shear Strength:**

17600 double pounds per square inch

**Material:**

Iron alloy 660

**Material Specification:**

Ams5737 assn standard single material response or ams5731 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Hi-shear spec. 258, cage 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

26512-gb511dk manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0