## NSN 5320-01-422-0658

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-422-0658 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.135 inches and 1.155 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3483 inches and 0.3488 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Solid film and cetyl alcohol **Grip Length:** Between 0.495 inches and 0.505 inches Min. Tensile Strength (psi): 6300 pounds per square inch **Thread Size:** 0.3125 inches **Shear Strength:** 18000 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Anodize **Thread Series Designator:** Unjf **Specification Data:** 26512-gb511bf manufacturers specification control Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-422-0658

Pin-rivet - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A528u0