

View Online at <https://aerobasegroup.com/nsn/5320-01-423-7569>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.697 inches and 0.717 inches

Head Style:

Err-090

Head Height:

Between 0.080 inches and 0.090 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.435 inches and 0.440 inches

Lubrication:

Solid film

Grip Length:

0.312 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Solid film lube surface coating

Material:

Titanium alloy

Material Specification:

Ams4928 assn standard single material response or ams4987 assn standard single material response

Surface Treatment Specification:

Hi-shear specification 306, type 2 mfr ref 1st treatment response and mil-l-8937 military specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-I-8937 spec.