NSN 5320-01-424-5079

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-424-5079

Identification Code Color:
Green
Fastener Length:
0.553 inches
Head Style:
Tapered pan
Head Height:
Between 0.125 inches and 0.135 inches
Shank Diameter:
Between 0.197 inches and 0.199 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.305 inches and 0.332 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.344 inches and 0.407 inches
Special Features:
Single action fastener installed with a single action tool
Material:
Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem
Material Specification:
Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams
5737 assn standard single material response sleeveams 5737 assn standard single material response stem
Surface Treatment:
Passivate mechanical lockpassivate sleeve or cadmium sleeve and chromate sleevepassivate stem
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response mechanical lockqq-p-35 federal specification 1st treatment response sleeve and
qq-p-416, type 2, cl 2 federal specification 2nd treatment response sleeve and qq-p-416, type 2, cl 2 federal specification 3rd treatment
response sleeveqq-p-35 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:
_
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-f-8975 spec.