

View Online at <https://aerobasegroup.com/nsn/5320-01-424-5080>

**Identification Code Color:**

Green

**Fastener Length:**

0.740 inches

**Head Style:**

Tapered pan

**Head Height:**

Between 0.125 inches and 0.135 inches

**Shank Diameter:**

Between 0.197 inches and 0.199 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.305 inches and 0.332 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.531 inches and 0.595 inches

**Special Features:**

Single action fastener installed with a single action tool

**Material:**

Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem

**Material Specification:**

Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem

**Surface Treatment:**

Passivate mechanical lockpassivate sleeve or cadmium sleeve and chromate sleevepassivate stem

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response mechanical lockqq-p-35 federal specification 1st treatment response sleeve and qq-p-416, type 2, cl 2 federal specification 2nd treatment response sleeve and qq-p-416, type 2, cl 2 federal specification 3rd treatment response sleeveqq-+35 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-f-8975 spec.