

View Online at <https://aerobasegroup.com/nsn/5320-01-424-5081>

**Fastener Length:**

0.781 inches

**Head Style:**

Tapered pan

**Head Height:**

Between 0.130 inches and 0.140 inches

**Shank Diameter:**

Between 0.258 inches and 0.260 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.400 inches and 0.432 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.531 inches and 0.595 inches

**Special Features:**

Single action fastener installed with a single action tool

**Material:**

Iron alloy 660 mechanical lock or steel comp 316 mechanical lock iron alloy 660 sleeve iron alloy 660 stem

**Material Specification:**

Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lock  
ams 5737 assn standard single material response sleeve ams 5737 assn standard single material response stem

**Surface Treatment:**

Passivate mechanical lock passivate sleeve or cadmium sleeve and chromate sleeve passivate stem

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response mechanical lock qq-p-35 federal specification 1st treatment response sleeve and  
qq-p-416, type 2, cl 2 federal specification 2nd treatment response sleeve and qq-p-416, type 2, cl 2 federal specification 3rd treatment  
response sleeve qq-p-35 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-f-8975 spec.