

View Online at <https://aerobasegroup.com/nsn/5320-01-424-5082>

Fastener Length:

0.844 inches

Head Style:

Tapered pan

Head Height:

Between 0.130 inches and 0.140 inches

Shank Diameter:

Between 0.258 inches and 0.260 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.400 inches and 0.432 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.594 inches and 0.647 inches

Special Features:

Single action fastener installed with a single action tool

Material:

Iron alloy 660 mechanical lock or steel comp 316 mechanical lock iron alloy 660 sleeve iron alloy 660 stem

Material Specification:

Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lock ams 5737 assn standard single material response sleeve ams 5737 assn standard single material response stem

Surface Treatment:

Passivate mechanical lock passivate sleeve or cadmium sleeve and chromate sleeve passivate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response mechanical lock qq-p-35 federal specification 1st treatment response sleeve and qq-p-416, type 2, cl 2 federal specification 2nd treatment response sleeve and qq-p-416, type 2, cl 2 federal specification 3rd treatment response sleeve qq-p-35 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-f-8975 spec.