

View Online at <https://aerobasegroup.com/nsn/5320-01-424-7958>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.288 inches and 1.308 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2021 inches and 0.2026 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Lubrication:

Solid film or dry film and cetyl alcohol

Grip Length:

Between 0.933 inches and 0.943 inches

Min. Tensile Strength (psi):

4350 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

8100 double pounds per square inch

Special Features:

0.0156 oversize, for repair work only

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

76301-st3-814 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0