

View Online at <https://aerobasegroup.com/nsn/5320-01-424-7958>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.288 inches and 1.308 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.2021 inches and 0.2026 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.357 inches and 0.377 inches

**Lubrication:**

Solid film or dry film and cetyl alcohol

**Grip Length:**

Between 0.933 inches and 0.943 inches

**Min. Tensile Strength (psi):**

4350 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

8100 double pounds per square inch

**Special Features:**

0.0156 oversize, for repair work only

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

76301-st3-814 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0