NSN 5320-01-425-6253

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Green

Thread Direction:

Fastener Length:

Identification Code Color:

Between 1.065 inches and 1.085 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-425-6253

Head Style:
Flush countersunk
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.1890 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.3765 inches and 0.3813 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.745 inches and 0.755 inches
Min. Tensile Strength (psi):
4350 pounds per square inch
Thread Size:
0.190 inches
Shear Strength:
7060 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Grit blast top of head with color green on thread end.
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Spec.258, cage 73197 mfr ref single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-425-6253

Pin-rivet - Page 2 of 2



\r	•	C 2 t	ınn	11212	Į
OL.		Cal	UII	Data	,

73197-hlt423 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0