NSN 5320-01-425-9724

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-425-9724 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.535 inches and 1.555 inches **Head Style:** Err-090 Width Between Flats: Between 0.1582 inches and 0.1616 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.7556 inches and 0.7604 inches Lubrication: Solid film or dry film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.995 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Countersink Angle:** 100.0 degrees Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5320-01-425-9724

Pin-rivet - Page 2 of 2



Fiig:

A528u0