## NSN 5320-01-426-3142

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-426-3142

View Online at https://aerobasegroup.com/nsn/5320-01-426-3142
Fastener Length:
Between 0.240 inches and 0.250 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.093 inches and 0.096 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.1263 inches and 0.1478 inches
Head Minor Diameter:
0.086 mils and 0.096 centimeters
Countersink Height:
Between 0.0089 inches and 0.0123 inches
Countersink Angle:
Between 70.0 degrees and 130.0 degrees
Heat Treatment:
T-4 solution heat treated
Material:
Aluminum alloy 2117
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, ty2, cl1 military specification single treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ040a0

Mil-a-8625 spec.

Mil-std (military Standard):