## NSN 5320-01-426-4106

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-426-4106

| View Online at https://aerobasegroup.com/nsn/5320-01-426-4106                                     |
|---|
| Thread Class:   |
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Identification Code Color:  |
| Blue  |
| Fastener Length:  |
| Between 2.2375 inches and 2.2575 inches   |
| Head Style:   |
| Err-090   |
| Head Height:  |
| Between 0.178 inches and 0.188 inches   |
| Width Between Flats:  |
| Between 0.2207 inches and 0.2242 inches   |
| Shank Diameter:   |
| Between 0.4990 inches and 0.4995 inches   |
| Shank Style:  |
| Pin-rivet, straight, threaded   |
| Head Major Diameter:  |
| Between 0.735 inches and 0.770 inches   |
| Lubrication:  |
| Cetyl alcohol, specification 305, hi-shear corp   |
| Grip Length:  |
| Between 1.5575 inches and 1.5675 inches   |
| Min. Tensile Strength (psi):  |
| 25500 pounds per square inch  |
| Thread Size:  |
| 0.500 inches  |
| Shear Strength:   |
| 37300 double pounds per square inch   |
| Special Features:   |
| Grit blast top of head, with color light blue on thread end.                                      |
| Material:   |
| Titanium alloy uns r56400   |
| Material Specification:   |
| Ams 4928 assn standard single material response or ams4967 assn standard single material response |
| Thread Series Designator:   |
| Unjf  |
| Specification Data:   |
| 73197-hlt452 manufacturers standard   |
| Shelf Life:   |

N/a

## NSN 5320-01-426-4106

Pin-rivet - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A528u0