NSN 5320-01-429-6609

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-429-6609

Fastener Length:
1.306 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.1970 inches and 0.1990 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
Between 0.2700 inches and 0.3016 inches
Expansion Device:
Threaded stem
Lubrication:
Dry film or cetyl alcohol or paraffin wax
Grip Length:
Between 0.845 inches and 0.906 inches
Features Provided:
Drive nut
Min. Tensile Strength (psi):
1250 pounds per square inch
Shear Strength:
4600 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Titanium alloy uns r56400 stem
Material Specification:
Qq-s-763 federal specification single material response sleeve or ams5639 assn standard single material response sleeve or ams5641 assi
standard single material response sleeve
Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response sleeve
Specification Data:
76823-03a053 manufacturers standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A040a0