# NSN 5320-01-429-6609

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-429-6609

# Fastener Length:

1.306 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.1970 inches and 0.1990 inches

# Shank Style:

Threaded self-plugging shank w/sleeve

## Head Major Diameter:

Between 0.2700 inches and 0.3016 inches

## Expansion Device:

Threaded stem

## Lubrication:

Dry film or cetyl alcohol or paraffin wax

## Grip Length:

Between 0.845 inches and 0.906 inches

## Features Provided:

Drive nut

## Min. Tensile Strength (psi):

1250 pounds per square inch

## Shear Strength:

4600 double pounds per square inch

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## Material:

Titanium alloy uns r56400 stem

## Material Specification:

Qq-s-763 federal specification single material response sleeve or ams5639 assn standard single material response sleeve or ams5641 assn

standard single material response sleeve

## Surface Treatment:

Passivate sleeve

#### **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response sleeve

#### Specification Data:

76823-03a053 manufacturers standard

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A040a0