

View Online at <https://aerobasegroup.com/nsn/5320-01-430-2889>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

7.000 inches

Head Style:

Err-090

Head Height:

0.050 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.292 inches and 0.322 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Unable To Decode:

Unable to decode and unable to decode

Grip Length:

0.375 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

To be used w/ hl79-6 hi-lok collar, not hs-15-6 collar

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0