

View Online at <https://aerobasegroup.com/nsn/5320-01-430-2889>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

7.000 inches

**Head Style:**

Err-090

**Head Height:**

0.050 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.292 inches and 0.322 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Unable To Decode:**

Unable to decode and unable to decode

**Grip Length:**

0.375 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

To be used w/ hl79-6 hi-lok collar, not hs-15-6 collar

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0