
# NSN 5320-01-432-2441

Pin-rivet - Page 1 of 2



**Thread Class:** 

3a

**Thread Direction:** 

Right-hand

# Fastener Length:

Between 0.503 inches and 0.523 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.064 inches and 0.074 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.2177 inches and 0.2182 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.357 inches and 0.377 inches

## Lubrication:

Cetyl alcohol or cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.183 inches and 0.193 inches

#### Min. Tensile Strength (psi):

2750 pounds per square inch

#### Thread Size:

0.190 inches

#### Shear Strength:

5380 double pounds per square inch

# **Special Features:**

Powder blast top of head. "caution" restricted usage. (for repair work only). 0.0312 oversize.

#### Material:

Titanium alloy uns r56400

# Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No



# NSN 5320-01-432-2441

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

