NSN 5320-01-432-2441

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-432-2441 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.503 inches and 0.523 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2177 inches and 0.2182 inches **Shank Style: Head Major Diameter:** Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol or cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.183 inches and 0.193 inches Min. Tensile Strength (psi): 2750 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 5380 double pounds per square inch **Special Features:** Powder blast top of head. "caution" restricted usage. (for repair work only). 0.0312 oversize. Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-432-2441

Pin-rivet - Page 2 of 2



Fiig:

A528u0