## NSN 5320-01-432-2670

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-432-2670



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.737 inches and 0.757 inches

### Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

## Width Between Flats:

Between 0.0947 inches and 0.0967 inches

## Shank Diameter:

Between 0.2802 inches and 0.2807 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.435 inches and 0.460 inches

## Lubrication:

Cetyl alcohol

Grip Length:

Between 0.307 inches and 0.317 inches

## Min. Tensile Strength (psi):

5820 pounds per square inch

## Thread Size:

0.250 inches

## Shear Strength:

9300 double pounds per square inch

## **Special Features:**

Powder blast top of head. "caution" restricted usage (for repair work only). 0.0312 oversize.

## Material:

Titanium alloy uns r56400

## Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

## Thread Series Designator:

Unjf

## **Specification Data:**

1w025-03a076 manufacturers standard

#### Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-01-432-2670

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

