## NSN 5320-01-432-2670

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-432-2670 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.737 inches and 0.757 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2802 inches and 0.2807 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.435 inches and 0.460 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.307 inches and 0.317 inches Min. Tensile Strength (psi): 5820 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch **Special Features:** Powder blast top of head. "caution" restricted usage (for repair work only). 0.0312 oversize. Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 1w025-03a076 manufacturers standard Shelf Life: N/a **Unit Of Measure:** 

## NSN 5320-01-432-2670

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0