NSN 5320-01-433-3326

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-433-3326

н	e۵	Ч	St	vi	6	•
	ca	u	υı	v	•	

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.093 inches and 0.097 inches

Head Major Diameter:

Between 0.175 inches and 0.183 inches

Expansion Device:

Serrated stem-type w

End Application:

Sw/s: helicopter, apache ah-64; f-22 raptor air dominance fighter; aircraft, harrier av-8b; aircraft, b-2 bomber (atb); aircraft, hornet f/a-18; gun system, 25mm; aviation ordnace; f/a-18e/f hornet aircraft; aircraft, eagle f-15

Grip Length:

Between 0.376 inches and 0.437 inches

Countersink Angle:

Between 98.5 degrees and 101.5 degrees

Material:

Nickel alloy 400 locking ring or nickel alloy r-405 locking ring

Material Specification:

Aqq-n-281 federal specification single material response locking ring

Surface Treatment:

Passivate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A040a0