## NSN 5320-01-433-5832

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-433-5832 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Black **Fastener Length:** 0.735 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches Lubrication: Cetyl alcohol **End Application:** B-2 bomber **Grip Length:** 0.375 inches Min. Tensile Strength (psi): 2000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 5380 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 

Shelf Life: N/a

76823-03a074 manufacturers standard

## NSN 5320-01-433-5832

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0