## NSN 5320-01-434-0101

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-434-0101

Fastener Length:
0.594 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.258 inches and 0.260 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.507 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.344 inches and 0.407 inches
Min. Tensile Strength (psi):
3650 pounds per square inch
Hardness Rating:
53.0 rockwell c stem
Shear Strength:
5900 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Single action fasteners installed with a single action tool.
Material:
Steel stem
Material Specification:
Astm-a-331 assn standard single material response stem
Surface Treatment:
Aluminum
Surface Treatment Specification:
Mil-c-83488 military specification single treatment response
Specification Data:
96906-ms90353 rev u government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A040a0

## NSN 5320-01-434-0101

Blind Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-c-83488 spec.