

View Online at <https://aerobasegroup.com/nsn/5320-01-434-0102>

**Fastener Length:**

0.506 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.310 inches and 0.312 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.634 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.219 inches and 0.282 inches

**Min. Tensile Strength (psi):**

5200 pounds per square inch

**Hardness Rating:**

48.0 rockwell c stem and 53.0 rockwell c stem

**Shear Strength:**

8500 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Single action fasteners installed with a single action tool.

**Material:**

Steel stem

**Material Specification:**

Astm-a-331 assn standard single material response stem

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Mil-c83488 military specification single treatment response

**Specification Data:**

96906-ms90353 rev. U government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

spec.