# NSN 5320-01-434-5891

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-434-5891

# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.818 inches and 1.843 inches

## Head Style:

Flush countersunk

## Shank Style:

Pin-rivet, tapered, threaded

## Head Major Diameter:

Between 0.888 inches and 0.971 inches

## Lubrication:

Cetyl alcohol

## Grip Length:

Between 1.365 inches and 1.380 inches

## **Thread Size:**

0.4375 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## Material:

Steel comp 8740 or steel comp 4340

# Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

## Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416, ty2, cl3 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

# Fiig:

A528u0

## Mil-std (military Standard):

Mil-s-6049 spec.

