NSN 5320-01-434-7620

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-434-7620 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.753 inches and 1.773 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.217 inches and 0.218 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.295 inches and 0.315 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.428 inches and 1.448 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 7100 double pounds per square inch Steel comp e4340 or steel comp 4140 or steel comp 8740 **Surface Treatment:** Cadmium **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-434-7620

Pin-rivet - Page 2 of 2



Fiig:

A528u0