# NSN 5320-01-434-8171

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-434-8171



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 2.2875 inches and 2.3125 inches

## Head Style:

Flush countersunk

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.998 inches and 1.087 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

Between 1.8025 inches and 1.8175 inches

#### **Thread Size:**

0.5000 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## Material:

Steel comp 8740 or steel comp 4340

## Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, ty2, cl3 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

## Fiig:

A528u0

## Mil-std (military Standard):

Mil-s-6049 spec.