# NSN 5320-01-434-8678

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-434-8678

### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

2.423 inches

# Head Style:

Flush countersunk

### Shank Diameter:

0.5608 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.998 inches and 1.087 inches

#### Tip Diameter:

## 0.5270 inches

Lubrication:

Cetyl alcohol

## Grip Length:

1.938 inches

## **Thread Size:**

0.500 inches

## Countersink Angle:

100.0 degrees

#### **Special Features:**

1/64 in oversize

Material:

Steel comp 4340 or steel comp 8740

#### Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## Thread Series Designator:

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-434-8678

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

